

# PANZERI

## East

220-240V AC  
XGR0997

● plaster



### Data sheet

CODE	XGR0997
SYSTEM POWER CONSUMPTION	max 50W
LIGHT SOURCE	LED retrofit / halogen
LIGHT SOURCE KIT	not included
COMPATIBLE SOURCES	max 50W GU10
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
WEIGHT	0,26 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	16,0 x 11,0 x 8,0 cm



Lighting fixture for ceiling or wall built-in installation for interiors, with direct light emission.

Total built-in plaster structure for plasterboard.

Light source retaining spring clip in stainless steel.

Micro-perforated sheet metal brackets for plasterboard fixing.

Built-in hole dimension: Ø 100mm (Ø 3,9")

### Technical drawing

Ø 6,3  
Ø 2 1/2"



Ø 9,8  
Ø 3 9/16"

12  
4 3/4"

12,5  
5"

13,5  
5 1/8"

14,5  
5 9/16"

Ø 10  
Ø 4"

### Application



# PANZERI

## East


### Accessories / source

---

YLL001.050.2201 PAR16 LED lamp GU10 7,5W 220-240V AC 3000K Ra>80 608lm 60°, not dimmable, white colour.



YLL002.050.2201 PAR16 LED lamp GU10 7,5W 220-240V AC 3000K Ra>80 608lm 60°, not dimmable, black colour.



YLS001.050.1715 LED lamp 8,5W 250mA 35V 2700K Ra>90 806lm 35°.



YLS001.050.2515 LED lamp 8,5W 250mA 35V 3000K Ra>90 854lm 35°.



YLS001.050.2915 LED lamp 8,5W 250mA 35V 4000K Ra>90 1053lm 35°.




# PANZERI

## East

### Accessories / power supply


XM6-15 UNI

LED driver, 2,5÷15W 60÷360mA.



XM6-20 D/P MULTI

LED driver, 9,2÷28W 200÷900mA, 1-10V/DALI/Push DIM dimmable.



XM6-25 D/P MULTI

LED driver, 11÷25,6W 200÷900mA, DALI/Push DIM dimmable.

