PANZERI

Step By Step

350mA DC

XGR1023





Data sheet

CODE	XGR1023
SYSTEM POWER CONSUMPTION	1W
EFFICACY	54lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>80
LIGHT DISTRIBUTION	asymmetric
POWER SUPPLY	350mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	120lm
LUMEN OUTPUT	54lm
EFFICIENCY	45%
WEIGHT	0,40 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	20,5 x 8,5 x 17,0 cm













Lighting fixture for ceiling or wall built-in installation for interiors, with direct light

Total built-in plaster structure for masonry or plasterboard.

Turned aluminium heat sink.

Acrylic moulded lens.

Light module closing frame in turned aluminium.


Light source retaining spring clip in stainless steel.

Fixing brackets in micro-perforated sheet metal.

 $\hbox{Recessed housing for masonry in galvanized sheet metal to be ordered separately}.$

Built-in hole dimension: 110x150mm (4,3x5,9")


Technical drawing



Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

PANZERI

Step By Step

Accessories / power supply

XM6-15 UNI	LED driver, 2,5÷15W 60÷360mA.	mm 61
CE EHI 🗵 🕪 👗		34 mm 1 1/6*
		115 mm 4 ½*
XM6-20 D/P MULTI	LED driver, 9,2÷28W 200÷900mA, 1-10V/DALI/Push DIM dimmable.	285 mm
CE FHI 🗵 🖦 🐔		www.stg.
		156 mm 8 ½*
XM6-25 D/P MULTI	LED driver, 11÷25,6W 200÷900mA, DALI/Push DIM dimmable.	uu 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1
CE FAIL X 🕸 🕸		2.88 mm
- 7		164 mm 61/s*

PANZERI

Step By Step

Accessories / fixing

XM1023/1026

Galvanized sheet housing to be recessed in brick wall or concrete.









