Queens 10

220-240V AC ON-OFF

XM748-12-01-3K





Data sheet

XM748-12-01-3K
12W
101.75lm/W
LED
L80 (B10) 50.000h
3000K Ra>90
adjustable
30°
220-240V AC
50/60Hz
ON-OFF
integrated included
1469lm
1221lm
83.1%
UGR < 11
0,50 Kg
IP20
850°
12,0 x 30,0 x 11,5 cm



Lighting fixture for electrified track for interiors, with swivelling light beam. Die-cast aluminium joint with powder paint.

Die-cast aluminium cap with powder paint.

Die-cast aluminium structure rotating on two axes in white or black powder paint.

Reflector in thermoplastic material with chrome plated finish.


Equipped with electric and mechanical adapter for three-phase electrified tracks.








Technical drawing



Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

Queens 10

Accessories / diffusion

Queens 10

Accessories / electrified tracks

XM7501-100

CE EHI 🗵

Three-phase electrified track for suspended or ceiling installation for interiors. Structure in anodized extruded aluminium or with white or black powder paint. Copper conductors housed inside extruded section bars in PVC with high isolation resistance. 230-250V AC line voltage or 380-440V AC industrial line voltage power supply. 16A total electrical load. Fastening, joining and closing accessories to be ordered separately. Length: 1m (39,4")



XM7501-200



Three-phase electrified track for suspended or ceiling installation for interiors. Structure in anodized extruded aluminium or with white or black powder paint. Copper conductors housed inside extruded section bars in PVC with high isolation resistance. 230-250V AC line voltage or 380-440V AC industrial line voltage power supply. 16A total electrical load. Fastening, joining and closing accessories to be ordered separately. Length: 2m (78,7")



XM7501-300



Three-phase electrified track for suspended or ceiling installation for interiors. Structure in anodized extruded aluminium or with white or black powder paint. Copper conductors housed inside extruded section bars in PVC with high isolation resistance. 230-250V AC line voltage or 380-440V AC industrial line voltage power supply. 16A total electrical load. Fastening, joining and closing accessories to be ordered separately. Length: 3m (118,1")



Queens 10

Accessories / electrified tracks / adapters

XM7501

Electro/mechanical adapter 6A, mechanical load 5kg, for three-phase electrified track.

C€ [HI 🗵

XM76B01

Mechanical adapter with automatic locking for three-phase electrified track.





C E EHI 🗵

Queens 10

Accessories / electrified tracks / power supply and closing

XM76ADX01

Right live-end for three-phase electrified track.







XM76ASX01

Left live-end for three-phase electrified track.





Queens 10

Accessories / electrified tracks / power supply and junction

XM76A01

C € EHI 🗵

Central connector and straight joint for three-phase electrified track.



Queens 10

Accessories / electrified tracks / closing

XM76C01

Cover 1000mm (39,4") long for three-phase electrified track.





XM76E01

End cap for three-phase electrified track.





Queens 10

Accessories / electrified tracks / fixing

XM76K

Ceiling kit for three-phase electrified track.





XM76S01

Suspension kit with 2m (78,7") long steel wire and plate for three-phase electrified track.





Queens 10

Accessories / electrified tracks / junction

Flexible joint for three-phase electrified track. XM76F01 C € EHE 🗵 External "L" joint for three-phase electrified track. XM76LE01 C € EHE 🗵 XM76LI01 Internal "L" joint for three-phase electrified track. C€ EHI 🗵 Mobile joint for three-phase electrified track. XM76M01 C€ EHI 🗵 XM76Q01 Electrical straight joint with stop for three-phase electrified track. CE EHI 🗵 XM76TDX01 Right "T" joint for three-phase electrified track. C EHI 🗵 XM76TSX01 Left "T" joint for three-phase electrified track. C€ EHI 🗵 XM76U01 Mechanical straight joint for three-phase electrified track. C€ EHI 🗵 XM76X01 "X" joint for three-phase electrified track. C € EHE 🗵