Queens 25

220-240V AC ON-OFF XM751-30-01-4K

Data sheet

CODE	XM751-30-01-4K
SYSTEM POWER CONSUMPTION	30W
EFFICACY	87.23lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	4000K Ra>85
LIGHT DISTRIBUTION	adjustable
BEAM ANGLE	29°
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	ON-OFF
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	3590lm
LUMEN OUTPUT	2617lm
EFFICIENCY	72.9%
GLARE RATING	UGR < 16
WEIGHT	1,04 Kg
PROTECTION DEGREE	IP20
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	11,0 x 11,7 x 29,2 cm

white





Lighting fixture for electrified track for interiors, with swivelling light beam. Die-cast aluminium joint with powder paint.


Die-cast aluminium cap with powder paint.

Die-cast aluminium structure rotating on two axes in white or black powder paint. Reflector in thermoplastic material with chrome plated finish.

Equipped with electric and mechanical adapter for three-phase electrified tracks.

CE EAE 🗵


Technical drawing



Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

Queens 25

Accessories / diffusion

XMR5 Ce ini X	Spot optic.	23 mm 1"
XMR7 Ceihi X	Wide flood optic.	23 mm 1"
XMR8 Ce ini X	Wide flood optic.	23 mm

1"

Queens 25

Accessories / electrified tracks

хм7501-100 ССЕЕНЦ 🗵	Three-phase electrified track for suspended or ceiling installation for interiors. Structure in anodized extruded aluminium or with white or black powder paint. Copper conductors housed inside extruded section bars in PVC with high isolation resistance. 230-250V AC line voltage or 380-440V AC industrial line voltage power supply. 16A total electrical load. Fastening, joining and closing accessories to be ordered separately. Length: 1m (39,4")	
хм7501-200 ССЕЕНЦ <u>х</u>	Three-phase electrified track for suspended or ceiling installation for interiors. Structure in anodized extruded aluminium or with white or black powder paint. Copper conductors housed inside extruded section bars in PVC with high isolation resistance. 230-250V AC line voltage or 380-440V AC industrial line voltage power supply. 16A total electrical load. Fastening, joining and closing accessories to be ordered separately. Length: 2m (78,7")	36 mm 13/r Wurster Burger
хм7501-300 ССЕЕНЦ	Three-phase electrified track for suspended or ceiling installation for interiors. Structure in anodized extruded aluminium or with white or black powder paint. Copper conductors housed inside extruded section bars in PVC with high isolation resistance. 230-250V AC line voltage or 380-440V AC industrial line voltage power supply. 16A total electrical load. Fastening, joining and closing accessories to be ordered separately. Length: 3m (118,1")	36 mm 13/r T DUB I D

Queens 25

Accessories / electrified tracks / adapters

XM7501

Electro/mechanical adapter 6A, mechanical load 5kg, for three-phase electrified track.



XM76B01

Mechanical adapter with automatic locking for three-phase electrified track.





Queens 25

Accessories / electrified tracks / power supply and closing

XM76ADX01

Right live-end for three-phase electrified track.

CE ERE 🗵



XM76ASX01

Left live-end for three-phase electrified track.





Queens 25

Accessories / electrified tracks / power supply and junction

XM76A01

Central connector and straight joint for three-phase electrified track.





Queens 25

Accessories / electrified tracks / closing

XM76C01

Cover 1000mm (39,4") long for three-phase electrified track.





XM76E01

End cap for three-phase electrified track.






Queens 25

Accessories / electrified tracks / fixing

XM76K

Ceiling kit for three-phase electrified track.





XM76S01

Suspension kit with 2m (78,7") long steel wire and plate for three-phase electrified track.





Queens 25

Accessories / electrified tracks / junction

XM76F01	Flexible joint for three-phase electrified track.	ass miles
XM76LE01	External "L" joint for three-phase electrified track.	
хм76LI01 ССЕП	Internal "L" joint for three-phase electrified track.	80 mm 3 %
хм76м01 ССЕП	Mobile joint for three-phase electrified track.	240°
хм76Q01 СС III 🗵	Electrical straight joint with stop for three-phase electrified track.	80 mm
XM76TDX01	Right "T" joint for three-phase electrified track.	120 mm 4 347
XM76TSX01	Left "T" joint for three-phase electrified track.	120 mm 4 347
хм76U01 ССЕЕНЦ	Mechanical straight joint for three-phase electrified track.	
хм76х01 С € ЕНГ 🗶	"X" joint for three-phase electrified track.	Teo mm