Brooklyn Out

24V DC

XP2033-100TRACK





Data sheet

CODE	XP2033-100TRACK
SYSTEM POWER CONSUMPTION	max 24W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
WEIGHT	0,68 Kg
PROTECTION DEGREE	IP20
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	6,0 x 6,0 x 114,0 cm
L (mm)	1025
L (in)	40 2/5"









Modular profile for suspended or ceiling installation for interiors, with direct light

Extruded aluminium structure in RAL 9003 white powder paint.

Extruded polycarbonate diffuser with opaline finish.

Light modules and driver to be ordered separately.

Connection, fastening, joining and closing accessories to be ordered separately.


Technical drawing












Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

Brooklyn Out

Accessories / source

XM006.012.0410

LED module, 125mm (5") 16 LED 2,2W 24V DC 3000K Ra>90 285lm.









XM006.050.0410

LED module, 500mm (19,7") 64 LED 8,6W 24V DC 3000K Ra>90 1140lm.









YLR002.017.0410

Strip LED, 5000mm (196,9") 168 LED/m 17,3W/m 24V DC 3000K Ra>90 1810lm/m, to be cut each 42mm (1,7").







YLR002.017.0610

Strip LED, 5000mm (196,9") 168 LED/m 17,3W/m 24V DC 4000K Ra>90 1920lm/m, to be cut each 42mm (1,7").







Strip LED, 5000mm (196,9") 168 LED/m 9,6W/m 24V DC 3000K Ra>90 930lm/m, to be cut each 42mm









Strip LED, 5000mm (196,9") 168 LED/m 9,6W/m 24V DC 2700K Ra>90 882lm/m, to be cut each 42mm (1,7").







YLR003.010.0610

Strip LED, 5000mm (196,9") 168 LED/m 9,6W/m 24V DC 4000K Ra>90 980lm/m, to be cut each 42mm (1,7").







Brooklyn Out

Accessories / power supply

Power supply kit with white canopy, 120W driver, power cable with lenght 2,2m (86,6"). XM2033-ST120W C€ [H[® Power supply kit with white canopy, 150W DALI/Push DIM dimmable driver, power cable with lenght XM2033-ST150W DIM 2,2m (86,6"). C€ EHI ŵ XM2033-T120W Power supply kit with white canopy and 120W driver. CE EHI ® Power supply kit with white canopy and 150W DALI/Push DIM dimmable driver. XM2033-T150W DIM CE EHI 🕸 LED driver, 4÷20W 250÷700mA. XM6-20 UNI C € ERI ŵ YDV.024.030.A01 LED driver, 30W 24V DC. C€ [H[ŵ LED driver, 120W 24V DC. YDV.024.120.A01 CE EHI ® LED driver, 180W 24V DC. YDV.024.180.A01

C € EHI ®

Brooklyn Out

Accessories / connection

XM2033/34/32/31-S

Power cables.





Brooklyn Out

Accessories / diffusion

XM2033/34-WHI

White reflector with 1000mm (39,4") lenght to be cut.



CE EHI ®

XM2033/34/45/46-1200S

Extruded polycarbonate diffuser with opaline finish, 12000mm (472,4") long.



C € ERI ®

XM2033/34/45/46-600S

Extruded polycarbonate diffuser with opaline finish, 6000mm (236,2") long.



C€ [H[ŵ



XM2033/34/45/46-900S

Extruded polycarbonate diffuser with opaline finish, 9000mm (354,3") long.







Brooklyn Out

Accessories / fixing

XM-KIT-S

Single suspension kit, with 2000mm (78 4/5") long steel wire.

XM231/32-P

Spacer for ceiling/wall installation.

Brooklyn Out

Accessories / junction

XM2033-A

Pair of adhesive light covers for junctions.

XM2033-U90 XP

Connection joint for two lines of modular profiles with level junction 90°, for suspended or ceiling installation.

XM2033/34-U

Linear junction.

XM2033/34-U

Linear junction.

Brooklyn Out

Accessories / closing

XM2033-T1

Pair of end caps with screws for suspended or ceiling mounted profiles.





