PANZERI

Nolita Out

220-240V AC dimmable (DALI/Push DIM)

XP23801.060.0402

white



Data sheet

CODE	XP23801.060.0402
SYSTEM POWER CONSUMPTION	24,5W
EFFICACY	54lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (DALI/Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	2608lm
LUMEN OUTPUT	1296lm
EFFICIENCY	49.7%
WEIGHT	1,48 Kg
PROTECTION DEGREE	IP40
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	14,0 x 65,0 x 14,0 cm
L (mm)	591
L (in)	23 2/7"



Modular profile for suspended or ceiling installation for interiors, with direct light

Extruded aluminium structure in RAL 9003 white powder paint.

Reflector retaining spring clips in stainless steel.

Aluminium reflector in RAL 9003 white polyacrylic paint.

Equipped with light modules and dimmable driver.

 ${\sf Extruded\ polycarbonate\ diffuser\ with\ opaline\ finish\ or\ micro-prismatic\ to\ be\ ordered}$ separately.


Connection, fastening, joining and closing accessories to be ordered separately.








Technical drawing





Application



Polar diagram

