PANZERI

Eddie

700mA DC

XR17201.030.1715





Data sheet

CODE	XR17201.030.1715
SYSTEM POWER CONSUMPTION	2,1W
EFFICACY	97lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	25°
POWER SUPPLY	700mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	210lm
LUMEN OUTPUT	194,6lm
EFFICIENCY	92.4%
WEIGHT	0,05 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm















Lighting fixture for ceiling built-in installation for interiors, with recessed direct light emission source.

Built-in structure for permanent false ceilings, with die-cast aluminium body and thin external frame in white or black powder paint.

Available in 2700K and 3000K version.

Stainless steel spring clips for false ceiling fixing.


Equipped with 0,4m (15,7") long power cable.

Built-in hole dimension: Ø 24mm (Ø 1").

Technical drawing










Application



Polar diagram



PANZERI

Eddie

Accessories / power supply