

# PANZERI

## Jessie

300mA DC  
XR17402.040.1715

● black



### Data sheet

CODE	XR17402.040.1715
SYSTEM POWER CONSUMPTION	5,2W
EFFICACY	97.2lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	24°
POWER SUPPLY	300mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	607lm
LUMEN OUTPUT	486lm
EFFICIENCY	80.1%
WEIGHT	0,12 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Lighting fixture for ceiling built-in installation for interiors, with recessed direct light emission source.

Die-cast aluminium structure in white and black powder paint, for permanent false ceilings, also of reduced dimensions, min.70mm (2,8").

24° beam optics available in white and black color.


Flush-mounting structure in white painted aluminium, with a snap-on coupling on the spotlight head for facilitating the installation.

Available in 2700K and 3000K version.

Equipped with 0,4m (15,7") long power cable.

Built-in hole dimension: Ø 43mm (Ø 1,7").


### Technical drawing



### Application



### Polar diagram




# PANZERI

Jessie

## Accessories / power supply

XM6-15 UNI

LED driver, 2,5÷15W 60÷360mA.



YDR.035.008.A02

LED driver, 8W 120÷350mA, DALI/Push DIM dimmable.

