PANZERI

James

300mA DC

XR17701.040.2515





Data sheet

CODE	XR17701.040.2515
SYSTEM POWER CONSUMPTION	5,2W
EFFICACY	92.4lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	24°
POWER SUPPLY	300mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	607lm
LUMEN OUTPUT	462lm
EFFICIENCY	76.1%
WEIGHT	0,13 Kg
PROTECTION DEGREE	IP44
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm













Lighting fixture for ceiling built-in installation for interiors, with max. 30 $^{\circ}$ adjustable light beam and recessed direct light emission source.

Built-in die-cast aluminuim structure for permanent false ceilings in white or black powder paint.

 24° beam optics available in white and black color.


Flush-mounting structure in white painted aluminium, with a snap-on coupling on the $\,$ spotlight head for facilitating the installation.

Available in 2700K and 3000K version.

Equipped with 0,4m (15,7") long power cable.

Built-in hole dimension: Ø 43mm (Ø 1,7").


Technical drawing



Application



Polar diagram



PANZERI

James

Accessories / power supply