PANZERI

Rally Trim

600mA DC

XR17801.007.2515





Data sheet

CODE	XR17801.007.2515
SYSTEM POWER CONSUMPTION	3,6W
EFFICACY	99lm/W
LIGHT SOURCE	LED
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	30°
POWER SUPPLY	600mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	360lm
LUMEN OUTPUT	297lm
EFFICIENCY	82.5%
WEIGHT	0,13 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM <3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm
















 $Rectangular\ lighting\ fixture\ for\ ceiling\ built-in\ installation\ for\ interiors,\ with\ recessed$ direct light emission made of LED lens with 30à light beam.

Built-in die-cast aluminium structure in iron grey finish, for permanent false ceilings. Available with white frame and black optics, in 2700K and 3000K versions.

Equipped with 0,4m (15,7") long power cable.

Built-in hole dimension: 66x37mm (2,6x1,5").


Technical drawing



Application



Polar diagram



PANZERI

Rally Trim

Accessories / power supply

