PANZERI

Nick

700mA DC

XR22501.050.2515





Data sheet

| CODE | XR22501.050.2515 |
|----------------------------|---------------------|
| SYSTEM POWER CONSUMPTION | 6,5W |
| EFFICACY | 75.83lm/W |
| LIGHT SOURCE | LED |
| LIGHT SOURCE LIFETIME | L80 (B10) 50.000h |
| COLOUR TEMPERATURE | 3000K Ra>90 |
| LIGHT DISTRIBUTION | flood |
| BEAM ANGLE | 26° |
| POWER SUPPLY | 700mA DC |
| DRIVER | remote not included |
| NOMINAL LUMINOUS FLUX | 650lm |
| LUMEN OUTPUT | 455lm |
| EFFICIENCY | 70% |
| WEIGHT | 0,09 Kg |
| PROTECTION DEGREE | IP65 IP20 |
| SHOCK RESISTANCE RATING | IK08 |
| GLOW WIRE TEST PERFORMANCE | 850° |
| PACKING DIMENSIONS | 7,5 x 7,5 x 8,0 cm |
| | |



Lighting fixture for ceiling built-in installation for interiors or exteriors, with direct light

 $\label{powder} \mbox{Built-in structure for permanent false ceilings, in die-cast aluminium in white powder}$ paint.

Reflector in thermoplastic material with chrome plated finish.

Silicone gasket.

Diffuser in thermoplastic material with mat finish.

Anti-glare snoot in black thermoplastic material.

Stainless steel spring clips for false ceiling fixing.

Equipped with 0,4m (15,7") long power cable. Built-in hole dimension: Ø 43mm (Ø 1,7")










Technical drawing

Ø 3,6 1 3/7"








Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270

PANZERI

Nick

Accessories / power supply

