# PANZERI

### Nick


700mA DC XR22501.050.2515

#### Data sheet

CODE	XR22501.050.2515
SYSTEM POWER CONSUMPTION	6,5W
EFFICACY	75.83lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	26°
POWER SUPPLY	700mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	650lm
LUMEN OUTPUT	455lm
EFFICIENCY	70%
WEIGHT	0,09 Kg
PROTECTION DEGREE	IP65 IP20
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	7,5 x 7,5 x 8,0 cm



#### **Technical drawing**



white





Lighting fixture for ceiling built-in installation for interiors or exteriors, with direct light emission. Built-in structure for permanent false ceilings, in die-cast aluminium in white powder


paint. Reflector in thermoplastic material with chrome plated finish. Silicone gasket. Diffuser in thermoplastic material with mat finish.

Anti-glare snoot in black thermoplastic material. Stainless steel spring clips for false ceiling fixing. Equipped with 0,4m (15,7") long power cable. Built-in hole dimension: Ø 43mm (Ø 1,7")

#### Application



#### Polar diagram



# PANZERI

### Nick

#### Accessories / power supply

XM6-20 D/P MULTI	LED driver, 9,2÷28W 200÷900mA, 1-10V/DALI/Push DIM dimmable.	255 mm
CE FAI 🗵 🐨 🌋		315.mm
		156 mm 8 %*
XM6-20 UNI	LED driver, 4÷20W 250÷700mA.	min 22 1 <sup>1</sup> /s <sup>2</sup> /
CEERI 🗵 🐵 🌋		127 E
		118 mm 4 2/a*
XM6-25 D/P MULTI	LED driver, 11÷25,6W 200÷900mA, DALI/Push DIM dimmable.	245.mm
CE FAI 🗵 💿 🚵		ting ting ting ting ting ting ting ting
		6 1/2*