PANZERI

Nick

500mA DC
XR25401.040.1815

white

DIRECT LIGHT


Data sheet

CODE	XR25401.040.1815
SYSTEM POWER CONSUMPTION	4,5W
EFFICACY	99.75lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	wide flood
BEAM ANGLE	60°
POWER SUPPLY	500mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	470lm
LUMEN OUTPUT	399lm
EFFICIENCY	84.9%
WEIGHT	0,07 Kg
PROTECTION DEGREE	IP43 IP20
SHOCK RESISTANCE RATING	IK07
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	7,5 x 7,5 x 8,0 cm



Lighting fixture for ceiling built-in installation for interiors, with direct light emission.
Built-in structure for permanent false ceilings, in die-cast aluminium in white powder paint.
Textured glass screen.
Anti-glare snoot in black thermoplastic material.
Stainless steel spring clips for false ceiling fixing.
Equipped with 0,3m (11,8") long power cable.
Built-in hole dimension: Ø 36mm (Ø 1,4")

Technical drawing



Application

Polar diagram

