PANZERI

Nick

500mA DC

XR25401.040.2615





Data sheet

CODE	XR25401.040.2615
SYSTEM POWER CONSUMPTION	4,5W
EFFICACY	106.25lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	wide flood
BEAM ANGLE	60°
POWER SUPPLY	500mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	500lm
LUMEN OUTPUT	425lm
EFFICIENCY	85%
WEIGHT	0,07 Kg
PROTECTION DEGREE	IP43 IP20
SHOCK RESISTANCE RATING	IK07
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	7,5 x 7,5 x 8,0 cm



Lighting fixture for ceiling built-in installation for interiors, with direct light emission. $\label{powder} \mbox{Built-in structure for permanent false ceilings, in die-cast aluminium in white powder}$ paint.

Textured glass screen.

Anti-glare snoot in black thermoplastic material. Stainless steel spring clips for false ceiling fixing. Equipped with 0,3m (11,8") long power cable.

Built-in hole dimension: Ø 36mm (Ø 1,4")











Technical drawing

Ø 2,6








Ø 4 1 ⁵/8"



Application



Polar diagram



cd/klm C0 - C180 - - - C90 - C270