PANZERI

Nick

250/350mA DC XR26201.060.2515

Data sheet

CODE	XR26201.060.2515
SYSTEM POWER CONSUMPTION	9W/12W
EFFICACY	70.22lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	38°
POWER SUPPLY	250/350mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	1090lm/1470lm
LUMEN OUTPUT	632lm/852lm
EFFICIENCY	58%
WEIGHT	0,29 Kg
PROTECTION DEGREE	IP43
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	12,0 x 16,0 x 10,5 cm








Lighting fixture for ceiling built-in installation for interiors, with direct light emission. Built-in structure for permanent false ceilings, in die-cast aluminium in white powder paint.

Reflector in thermoplastic material with chrome plated finish. Closing screen in transparent UV-resistant thermoplastic material. Anti-glare snoot in black thermoplastic material. Stainless steel spring clips for false ceiling fixing. Equipped with 0,4m (15,7") long power cable. Built-in hole dimension: Ø 64mm (Ø 2,5")

Technical drawing

CEERE 🗵 💮






Application



Polar diagram



PANZERI

Nick

Accessories / power supply

XM6-20 D/P MULTI	LED driver, 9,2÷28W 200÷900mA, 1-10V/DALI/Push DIM dimmable.	Min 12
CE ERE 🗵 💿 👗		21.5 mm
		156 mm 8 %/*
XM6-20 UNI	LED driver, 4÷20W 250÷700mA.	mi Si
CE EAE 🗵 💿 🌋		<u>اللہ 28</u>
		118 mm 4 1/a*
XM6-25 D/P MULTI	LED driver, 11÷25,6W 200÷900mA, DALI/Push DIM dimmable.	1
CE ERE 🗵 💿 👗		8 2 -
		6 1/2"

PANZERI

Nick

Accessories / diffusion

XMR5 CC [H] 🖄 🐵 🏔	Spot optic.	23 mm 1"
xmr6 CC [fii] 🖄 🐵 🚵	Flood optic.	23 mm 1"
XMR9	Internal satin gold cylinder.	
CE ERE 🗵 🐵 👗		