PANZERI

Nick

250/350mA DC

XR26201.060.2515





Data sheet

CODE	XR26201.060.2515
SYSTEM POWER CONSUMPTION	9W/12W
EFFICACY	70.22lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>90
LIGHT DISTRIBUTION	flood
BEAM ANGLE	38°
POWER SUPPLY	250/350mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	1090lm/1470lm
LUMEN OUTPUT	632lm/852lm
EFFICIENCY	58%
WEIGHT	0,29 Kg
PROTECTION DEGREE	IP43
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	12,0 x 16,0 x 10,5 cm



Lighting fixture for ceiling built-in installation for interiors, with direct light emission. Built-in structure for permanent false ceilings, in die-cast aluminium in white powder paint.

Reflector in thermoplastic material with chrome plated finish. Closing screen in transparent UV-resistant thermoplastic material. Anti-glare snoot in black thermoplastic material. Stainless steel spring clips for false ceiling fixing. Equipped with 0,4m (15,7") long power cable. Built-in hole dimension: Ø 64mm (Ø 2,5")










Technical drawing




Ø 5,9



Application



Polar diagram



PANZERI

Nick

Accessories / power supply



PANZERI

Nick

Accessories / diffusion

XMR5 Spot optic.

CE FILL A way for a spot optic.

XMR6 Flood optic.

CE FILL A way for a spot optic.

23 mm 1"

23 mm 1"

23 mm 1"

XMR9 Internal satin gold cylinder.

CE HI Z m