# **PANZERI**

### Bella

220-240V AC ON-OFF





#### Data sheet

CODE         L05201.011.0501           SYSTEM POWER CONSUMPTION         6,5W           EFFICACY         64.67lm/W           LIGHT SOURCE         LED           LIGHT SOURCE LIFETIME         L80 (B10) 70.000h           COLOUR TEMPERATURE         2700K Ra>90           LIGHT DISTRIBUTION         diffused           POWER SUPPLY         220-240V AC           FREQUENCY         50/60Hz           ELECTRICAL CONFIGURATION         ON-OFF           DRIVER         integrated included           NOMINAL LUMINOUS FLUX         460lm           LUMEN OUTPUT         388lm           EFFICIENCY         84.3%           WEIGHT         0,55 Kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3           PACKING DIMENSIONS         13,0 x 24,0 x 12,0 cm		
EFFICACY         64.67lm/W           LIGHT SOURCE         LED           LIGHT SOURCE LIFETIME         L80 (B10) 70.000h           COLOUR TEMPERATURE         2700K Ra>90           LIGHT DISTRIBUTION         diffused           POWER SUPPLY         220-240V AC           FREQUENCY         50/60Hz           ELECTRICAL CONFIGURATION         ON-OFF           DRIVER         integrated included           NOMINAL LUMINOUS FLUX         460lm           LUMEN OUTPUT         388lm           EFFICIENCY         84.3%           WEIGHT         0,55 Kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	CODE	L05201.011.0501
LIGHT SOURCE         LED           LIGHT SOURCE LIFETIME         L80 (B10) 70,000h           COLOUR TEMPERATURE         2700K Ra>90           LIGHT DISTRIBUTION         diffused           POWER SUPPLY         220-240V AC           FREQUENCY         50/60Hz           ELECTRICAL CONFIGURATION         ON-OFF           DRIVER         integrated included           NOMINAL LUMINOUS FLUX         460lm           LUMEN OUTPUT         388lm           EFFICIENCY         84.3%           WEIGHT         0,55 Kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	SYSTEM POWER CONSUMPTION	6,5W
LIGHT SOURCE LIFETIME         L80 (B10) 70.000h           COLOUR TEMPERATURE         2700K Ra>90           LIGHT DISTRIBUTION         diffused           POWER SUPPLY         220-240V AC           FREQUENCY         50/60Hz           ELECTRICAL CONFIGURATION         ON-OFF           DRIVER         integrated included           NOMINAL LUMINOUS FLUX         460lm           LUMEN OUTPUT         388lm           EFFICIENCY         84.3%           WEIGHT         0,55 Kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	EFFICACY	64.67lm/W
COLOUR TEMPERATURE         2700K Ra>90           LIGHT DISTRIBUTION         diffused           POWER SUPPLY         220-240V AC           FREQUENCY         50/60Hz           ELECTRICAL CONFIGURATION         ON-OFF           DRIVER         integrated included           NOMINAL LUMINOUS FLUX         460Im           LUMEN OUTPUT         388Im           EFFICIENCY         84.3%           WEIGHT         0,55 Kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	LIGHT SOURCE	LED
LIGHT DISTRIBUTION         diffused           POWER SUPPLY         220-240V AC           FREQUENCY         50/60Hz           ELECTRICAL CONFIGURATION         ON-OFF           DRIVER         integrated included           NOMINAL LUMINOUS FLUX         460lm           LUMEN OUTPUT         388lm           EFFICIENCY         84.3%           WEIGHT         0.55 Kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
POWER SUPPLY         220-240V AC           FREQUENCY         50/60Hz           ELECTRICAL CONFIGURATION         ON-OFF           DRIVER         integrated included           NOMINAL LUMINOUS FLUX         460lm           LUMEN OUTPUT         388lm           EFFICIENCY         84.3%           WEIGHT         0,55 Kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	COLOUR TEMPERATURE	2700K Ra>90
### FREQUENCY	LIGHT DISTRIBUTION	diffused
ELECTRICAL CONFIGURATION ON-OFF  DRIVER integrated included  NOMINAL LUMINOUS FLUX 460 lm  LUMEN OUTPUT 388 lm  EFFICIENCY 84.3%  WEIGHT 0,55 Kg  PROTECTION DEGREE IP40  COLOUR TOLLERANCES SDCM 3	POWER SUPPLY	220-240V AC
DRIVER integrated included  NOMINAL LUMINOUS FLUX 460Im  LUMEN OUTPUT 388Im  EFFICIENCY 84.3%  WEIGHT 0,55 Kg  PROTECTION DEGREE IP40  COLOUR TOLLERANCES SDCM 3	FREQUENCY	50/60Hz
NOMINAL LUMINOUS FLUX         460lm           LUMEN OUTPUT         388lm           EFFICIENCY         84.3%           WEIGHT         0.55 kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	ELECTRICAL CONFIGURATION	ON-OFF
LUMEN OUTPUT         388Im           EFFICIENCY         84.3%           WEIGHT         0.55 Kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	DRIVER	integrated included
EFFICIENCY         84.3%           WEIGHT         0,55 kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	NOMINAL LUMINOUS FLUX	460lm
WEIGHT         0,55 kg           PROTECTION DEGREE         IP40           COLOUR TOLLERANCES         SDCM 3	LUMEN OUTPUT	388lm
PROTECTION DEGREE IP40  COLOUR TOLLERANCES SDCM 3	EFFICIENCY	84.3%
COLOUR TOLLERANCES SDCM 3	WEIGHT	0,55 Kg
	PROTECTION DEGREE	IP40
PACKING DIMENSIONS 13,0 x 24,0 x 12,0 cm	COLOUR TOLLERANCES	SDCM 3
	PACKING DIMENSIONS	13,0 x 24,0 x 12,0 cm



Suspension lighting fixture for interiors, with direct light emission.

 $\label{eq:decomposition} \mbox{Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic}$ 

Modelled acrylic diffuser with mat finish.

Aluminium closing disk in polyacrylic paint.

Suspension kit with rod in brass tube in polyacrylic paint.

3m (118,1") long suspension and coaxial power cable in transparent PVC.


Power canopy with pickled sheet metal ceiling bracket and extruded aluminium  $\,$ covering in white, black, bronze, mat brass or titanium polyacrylic paint.








#### **Technical drawing**





#### Polar diagram



# **PANZERI**

## Bella

### Accessories / diffusion

YPL05207.015

C E EHI 🗵

Ivory pleated fabric lampshade, simple snap installation.







