#### Bella

24V DC M05201.011.0510

#### Data sheet

CODE	M05201.011.0510
SYSTEM POWER CONSUMPTION	4.5W
EFFICACY	97lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	460lm
LUMEN OUTPUT	388lm
EFFICIENCY	84.3%
WEIGHT	0,22 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	13,0 x 24,0 x 12,0 cm




Multiple suspension lighting fixture for interiors, with direct light emission. Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic paint.


Modelled acrylic diffuser with mat finish.

Aluminium closing disk in polyacrylic paint.

Suspension kit with rod in brass tube in polyacrylic paint.


3m (118,1") long suspension and coaxial power cable in transparent PVC. Provided without power canopy, complete with cable clamp on the cable's free extremity.





#### Polar diagram

white



# CEERE 🗵 🐵

### Bella

Accessories / power supply

хм100/24 dim С є ЕНС 🗵 🐵	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	E Contraction of the second se
хм150/24 DIM С Є ЕПП 🗵 💮	LED driver, 150W 24V DC, DALI/Push DIM dimmable.	
хм18/24 DIM С Є ЕНЦ 🖄 🖤	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	0 100 0 000 0 100 0
хм35/24 DIM С Є ІПІ 🗵 💮	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	90 gg 10 T 10 g mm 7 0/*
xm6-20 UNI C € EAL ▲ @ xm60/24 DIM C € EAL ▲ @	LED driver, 4÷20W 250÷700mA. LED driver, 60W 24V DC, DALI/Push DIM dimmable.	100 22 mm 2
YDV.024.030.A01	LED driver, 30W 24V DC.	22 mm 875
YDV.024.120.A01 CEEHL X	LED driver, 120W 24V DC.	and the second s
YDV.024.180.A01	LED driver, 180W 24V DC.	₽ ₽

### Bella

Accessories / power supply and fixing

XM8901-09	Canopy for power supply with 9 outputs.	3.8 1/2 1/2
CE EAL 🛓 🐵		· · · · · · · · · · · · · · · · · · ·
		28 4//*
XM8901-15	Canopy for power supply with 15 outputs.	
CE EAL 🗵 🐵		· · · · · · · · · · · · · · · · · · ·
XM9001-03	Canopy for power supply with 3 outputs.	0,-   
CEERI 🗵 🐵		39,5 15 4/2"
XM9001-07	Canopy for power supply with 7 outputs.	
CEER		39,5 15 4//*
XM9001-12	Canopy for power supply with 12 outputs.	0,111 0,111
CE EAL 🗵 🐵		22.4%
хм9201-01 С Є ЕНІ 🗵 🐵	Recessed canopy for electric cable suspensions. Suitable for 24V fixtures: remote driver 24V needed.	

### Bella

#### Accessories / diffusion

YPL05207.015



Ivory pleated fabric lampshade, simple snap installation.

