PANZERI

Bella

24V DC

M05301.011.0510





Data sheet

CODE	M05301.011.0510
SYSTEM POWER CONSUMPTION	4,5W
EFFICACY	97lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 70.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	460lm
LUMEN OUTPUT	388lm
EFFICIENCY	84.3%
WEIGHT	0,22 Kg
PROTECTION DEGREE	IP40
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	13,0 x 24,0 x 12,0 cm











Multiple suspension lighting fixture for interiors, with indirect light emission. $\label{eq:decomposition} \mbox{Die-cast aluminium structure in white, black, bronze, mat brass or titanium polyacrylic}$

Modelled acrylic diffuser with mat finish.


Pickled sheet metal closing disk in polyacrylic paint.


Suspension kit with rod in brass tube in polyacrylic paint.

3m (118,1") long suspension and coaxial power cable in transparent PVC.

Provided without power canopy, complete with cable clamp on the cable's free extremity.

Technical drawing





PANZERI

Bella

Accessories / power supply

,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	•	
XM100/24 DIM	LED driver, 100W 24V DC, DALI/Push DIM dimmable.	
C€ [EHI] <u>X</u> ŵ		1162
XM150/24 DIM	LED driver, 150W 24V DC, DALI/Push DIM dimmable.	}: □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
CE III 🗵 瞰		20 mm 5 mg -
XM18/24 DIM	LED driver, 18W 24V DC, DALI/Push DIM dimmable.	202.2 mg
		(5) (5) (7) (7) (7) (7) (7) (7) (7) (7) (7) (7
XM35/24 DIM	LED driver, 35W 24V DC, DALI/Push DIM dimmable.	
XM6-20 UNI	LED driver, 4÷20W 250÷700mA.	72 mm 1/4**
CE EHI X m		20 118 mm 4 3/s*
XM60/24 DIM	LED driver, 60W 24V DC, DALI/Push DIM dimmable.	
		2/3 nm 8/9"
YDV.024.030.A01	LED driver, 30W 24V DC.	
		Sit no. Sit o
YDV.024.120.A01	LED driver, 120W 24V DC.	
		Shift ever so the first section of the first sectio
YDV.024.180.A01	LED driver, 180W 24V DC.	<u>\$</u> ≥ \$k.
CE EHL 🗵 瞰		31 mm V Mr

PANZERI

Bella

Accessories / power supply and fixing

