



ACOUSTIC LIGHTING INSTALLATION GUIDE

2020

INSTRUCTIONS For Assembling and Installing Fixtures Pour l'assemblage et L'installation

Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

NORTH AMERICA

CODE	CANOPY LOCATIONS	CANOPY INFORMATION	CEILING MOUNT	ADDITIONAL INFO	REMOTE DRIVER		CONCEALED DRIVER		ON-BOARD DRIVER
					DRIVER SCHEMATICS	INSTALLATION INSTRUCTIONS	DRIVER SCHEMATICS	INSTALLATION INSTRUCTIONS	INSTALLATION INSTRUCTIONS
VE-S/M/L	3	14, 15, 16	17	33	18	19, 20	21, 22	23, 24, 25, 26	30, 31
VER-S/M/L	4	14, 15, 16	17	-	18	19, 20	21, 22	23, 24, 25, 26	30, 31
MA-3/5	5	14, 15, 16	17	-	18	19, 20	21, 22	23, 24, 25, 26	30, 31
SH-S/M/L	6	14, 15, 16	17	-	18	19, 20	21, 22	23, 24, 25, 26	30, 31
BC-S/M/L	7	14, 15, 16	17	-	18	19, 20	21, 22	23, 24, 25, 26	30, 31
LN-S/M/L/XL	8	14, 15, 16	17	-	18	19, 20	21, 22	23, 24, 25, 26	30, 31
BL-S/M/L/XL	9	14, 15, 16	17	-	18	19, 20	21, 22	23, 24, 25, 26	30, 31
DA-S/M/L/XL	10	14, 15, 16	17	-	18	19, 20	21, 22	23, 24, 25, 26	30, 31
AC	11	14, 15, 16	17	-	18	19, 20	21, 22	23, 24, 25, 26	30, 31
DG	12	14, 15, 16	17		18	19, 20	21, 22	23, 24, 25, 26	30, 31
HH-S/M	13	14, 15, 16	17	-	18	19, 20	21, 22	23, 24, 25, 26	30, 31


GLOBAL

CODE	CANOPY LOCATIONS	CANOPY INFORMATION	CEILING MOUNT	ADDITIONAL INFO	REMOTE DRIVER		CONCEALED DRIVER		ON-BOARD DRIVER
					DRIVER SCHEMATICS	INSTALLATION INSTRUCTIONS	DRIVER SCHEMATICS	INSTALLATION INSTRUCTIONS	INSTALLATION INSTRUCTIONS
VE-S/M/L	3	14, 15, 16	17	33	27	28, 29	21, 22	23, 24, 25, 26	32, 33
VER-S/M/L	4	14, 15, 16	17	-	27	28, 29	21, 22	23, 24, 25, 26	32, 33
MA-3/5	5	14, 15, 16	17	-	27	28, 29	21, 22	23, 24, 25, 26	32, 33
SH-S/M/L	6	14, 15, 16	17	-	27	28, 29	21, 22	23, 24, 25, 26	32, 33
BC-S/M/L	7	14, 15, 16	17	-	27	28, 29	21, 22	23, 24, 25, 26	32, 33
LN-S/M/L/XL	8	14, 15, 16	17	-	27	28, 29	21, 22	23, 24, 25, 26	32, 33
BL-S/M/L/XL	9	14, 15, 16	17	-	27	28, 29	21, 22	23, 24, 25, 26	32, 33
DA-S/M/L/XL	10	14, 15, 16	17	-	27	28, 29	21, 22	23, 24, 25, 26	32, 33
AC	11	14, 15, 16	17	-	27	28, 29	21, 22	23, 24, 25, 26	32, 33
DG	12	14, 15, 16	17		27	28, 29	21, 22	23, 24, 25, 26	32, 33
HH-S/M	13	14, 15, 16	17	-	27	28, 29	21, 22	23, 24, 25, 26	32, 33


Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

TOP VIEWS


SMALL



MEDIUM




LARGE




Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

TOP VIEWS


SMALL



MEDIUM




LARGE




TOP VIEWS

MEDIUM




LARGE




Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

TOP VIEWS


SMALL



MEDIUM




LARGE




Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

TOP VIEWS


SMALL



MEDIUM





LARGE




Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

TOP VIEWS


SMALL




MEDIUM



LARGE





EXTRA-LARGE




TOP VIEWS


SMALL




MEDIUM



LARGE




EXTRA-LARGE




SIDE VIEWS


SMALL




MEDIUM



LARGE




EXTRA-LARGE




Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9



TOP VIEWS




Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9




SIZE (Diameter)*	SUSPENSIONS POINTS	SECTIONS	PCD	Outside Diameter	Inside Diameter
23.6" - 600mm	4	1	23.6" - 600mm	25.9" - 660mm	21.2" - 540mm
31.5" - 800mm	4	1	31.5" - 800mm	31.5" - 860mm	29.1" - 740mm
35.4" - 900mm	4	1	35.4" - 900mm	37.8" - 960mm	33" - 840mm
39.3" - 1000mm	4	1	39.3" - 1000mm	41.7" - 1060mm	37" - 940mm
44.9" - 1140mm	4	1	44.9" - 1140mm	47.2" - 1200mm	42.5" - 1080mm
59" - 1500mm	4	4	59" - 1500mm	61.4" - 1560mm	56.7" - 1440mm
70.8" - 1800mm	4	4	70.8" - 1800mm	73.2" - 1860mm	68.5" - 1740mm
78.7" - 2000mm	4	4	78.7" - 2000mm	81.1" - 2060mm	76.4" - 1940mm



ceiling canopy - AUS



ceiling canopy - US



	NORTH AMERICA			GLOBAL		
PRODUCT	Remote Driver	Concealed Driver	On-Board Driver	Remote Driver	Concealed Driver	On-Board Driver
LX-VE-L	SA	CD13	SA	SB	CD13	SB
LX-VE-L-DI	SA	CD11	SA	SB	CD11	SB
LX-VE-M	SA	CD13	SA	SB	CD13	SB
LX-VE-M-DI	SA	CD11	SA	SB	CD11	SB
LX-VE-S	SA	CD11	SA	SB	CD11	SB
LX-VE-S-DI	SA	CD11	SA	SB	CD11	SB
LX-BC-L/M/S	SA	CD11	SA	SB	CD11	SB
LX-SI-L/M/S	SA	CD11	SA	SB	CD11	SB
LX-VER-L	SA	CD11	SA	SB	CD11	SB
LX-VER-L-DI	SA	CD13	SA	SB	CD13	SB
LX-VER-M	SA	CD11	SA	SB	CD11	SB
LX-VER-M-DI	SA	CD13	SA	SB	CD13	SB
LX-VER-S	SA	CD11	SA	SB	CD11	SB
LX-VER-S-DI	SA	CD11	SA	SB	CD11	SB
LX-MA-5	SA	CD11	SA	SB	CD11	SB
LX-MA-5-DI	SA	CD13	SA	SB	CD13	SB
LX-MA-3	SA	CD11	SA	SB	CD11	SB
LX-MA-3-DI	SA	CD11	SA	SB	CD11	SB
LX-DA-XL/L/M/S	SA	CD11	SA	SB	CD11	SB
LX-AC	SA	-	SA	SB	-	SB
LX-DG	SA	DGC	SA	SB	DGC	SB
LX-BL-XL/L/M/S	SA	CD11	-	SB	CD11	-
LX-LN	-	-	SA	-	-	SB
LX-WP-U-XL/L/M/S	SA	CD11	-	SB	CD11	-
LX-WP-D-XL/L/M	SA	CD11	-	SB	CD11	-
LX-HH-M/S	SA	-	-	SB	-	-
LX-PL-L/M/S	SA	-	-	SB	-	-
LX-NP	SA	-	-	SB	-	-

	INDEX FOR CANOPY INFORMATION				
CANOPY	SA	SB	CD11	CD13	CDG
PAGE	15	15	16	16	TBC


Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9



CANOPY DIMENSIONS


REMOTE AND ON-BOARD OPTIONS

SB CANOPY (GLOBAL)



1.96" / 50mm

BOTTOM VIEW



2.36" / 60mm

SIDE VIEW




6" / 25mm

TOP VIEW




RENDERED VIEW

SA CANOPY (NORTH AMERICA)




4.7" / 120mm

BOTTOM VIEW



1.77" / 45mm

SIDE VIEW




more detailed
dimensions below

TOP VIEW



RENDERED VIEW

MOUNTING PLATE PATTERN (NORTH AMERICA)



PCD: 3.5" / 89mm

PCD: 2.75" / 70mm


PCD: 2.16" / 55mm

Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9




LUXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXBOX.COM
LUXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXBOX.COM
WWW.LUXBOX.COM

CD11 CANOPY (GLOBAL / NORTH AMERICA)




11" / 280mm

BOTTOM VIEW




3.42" / 87mm

SIDE VIEW




more detailed dimensions on previous page

TOP VIEW




CD 13 (GLOBAL / NORTH AMERICA)




13" / 330mm

BOTTOM VIEW




3.42" / 87mm


SIDE VIEW



more detailed dimensions on previous page

TOP VIEW





DRIVER SCHEMATICS (REMOTE DRIVER INSTALLATION)

*Please refer to driver and accompanying documentation for further information regarding installation / wiring.




Caution, risk of electric shock

⚠ All electrical work, including the installation and wiring of drivers to be completed by a licensed electrician.

1. Line Voltage / Mains Power
2. DC Output
3. Dimming Control

OTHER INFORMATION

- Indoor use only
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person




WIRE COLOURS

- Hot/Live: Black
- Neutral: White
- Ground: Green
- Dimming Positive (+): Purple or as per wire label
- Dimming Negative (-): Grey or as per wire label
- Output (+): Red or as per wire label
- Output (-): Black or as per wire label

Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

⚠ This product is to be installed by a qualified electrician only




Caution, risk of electric shock




Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

REMOTE DRIVER INSTALLATION (NORTH AMERICA)


① (Full driver schematics on page 17)




② (Full instructions on page 16)




③




④



⑤




⑥



⚠ This product is to be installed by a qualified electrician only

⚠ Before starting, determine which fasteners will be best suited to secure the fitting, based on the material of the ceiling substrate.

1. Terminate Line Voltage (A) / Dimming Control (C) to remotely mounted LED driver. (B) DC output.
2. Hang shade from ceiling using mounting hardware provided. See page 14 for additional detail.
3. Mount canopy base to ceiling.
4. Insert DC output (A) from Driver into canopy base, then insert the DC input (B) from pendant or light source through canopy cover.
5. Terminate DC input to DC output inside canopy.
6. Place canopy cover over canopy base (A), then fasten grub screws (B) and cable strain relief (C).



Caution, risk of electric shock



Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

DRIVER SCHEMATICS (REMOTE DRIVER INSTALLATION)

*Please refer to driver and accompanying documentation for further information regarding installation / wiring.




Caution, risk of electric shock

⚠ All electrical work, including the installation and wiring of drivers to be completed by a licensed electrician.

1. Line Voltage / Mains Power
2. DC Output
3. Dimming Control

OTHER INFORMATION

- Indoor use only
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person



WIRE COLOURS (TBC)

- Hot/Live: Black
- Neutral: White
- Ground: Green
- Dimming Positive (+): Purple or as per wire label
- Dimming Negative (-): Grey or as per wire label
- Output (+): Red or as per wire label
- Output (-): Black or as per wire label

Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

DRIVER SCHEMATICS (CANOPY CONCEALED DRIVER OPTION)

*Please refer to driver and accompanying documentation for further information regarding installation / wiring.




Caution, risk of electric shock

⚠ All electrical work, including the installation and wiring of drivers to be completed by a licensed electrician.

1. Line Voltage / Mains Power
2. DC Output
3. Dimming Control

OTHER INFORMATION


- Indoor use only
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person



WIRE COLOURS


- Hot/Live: Brown
- Neutral: Blue
- Ground: Green / Yellow
- Dimming Positive (+): As per wire label
- Dimming Negative (-): As per wire label
- Output (+): Red or as per wire label
- Output (-): Black or as per wire label

Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9




*Standard 4" Junction Box (not included)

CANOPY DIMENSIONS




Isometric Views




Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

CANOPY CONCEALED DRIVER INSTALLATION (NORTH AMERICA)


① (Full driver schematics on page 20)




② (Full instructions schematics on page 16)




③




④



⑤




⑥



⚠ Before starting, determine which fasteners will be best suited to secure the fitting, based on the material of the ceiling substrate.


1. Insert main power cable through Canopy Base and screw this to Standard Junction Box.
2. Hang shade from ceiling using mounting hardware provided. See page 14 for additional detail.
3. Fix driver mounting plate to driver using the nuts provided
4. Licensed electrician to terminate Mains Power to Driver Input and DC output form Driver to lighting pendant. Driver schematics on pg. 26
5. Fix Driver to Canopy Base using the screws provided.
6. Place Canopy Cover over Canopy Base (A), then fasten set screws provided (B) and cable strain relief (C)



Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9




CANOPY CONCEALED INSTALLATION

MEANWELL (NORTH AMERICA)




*Standard 4" Junction Box (not included)

CANOPY DIMENSIONS




Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

CANOPY CONCEALED DRIVER INSTALLATION (NORTH AMERICA)



⚠ Before starting, determine which fasteners will be best suited to secure the fitting, based on the material of the ceiling substrate.

1. Hang shade from ceiling using mounting hardware provided. See page 14 for additional detail.
2. Insert main power and dimming cables through Canopy Base. Licensed electrician to terminate Mains power to Driver Input. Driver schematics on pg. 30
3. Licensed electrician to terminate Dimming to Driver Output and Dc Output to lighting pendant. Driver schematics on pg. 30
4. We recommend the use of twist-on wire connectors.
5. Fix Driver to Canopy Base using the screws provided.
6. Place Canopy Cover over Canopy Base (A), then fasten set screws provided (B) and cable strain relief (C)



Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9

DRIVER SCHEMATICS (REMOTE DRIVER INSTALLATION)

*Please refer to driver and accompanying documentation for further information regarding installation / wiring.




Caution, risk of electric shock

⚠ All electrical work, including the installation and wiring of drivers to be completed by a licensed electrician.

1. Line Voltage / Mains Power
2. DC Output
3. Dimming Control

OTHER INFORMATION


- Indoor use only
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person



WIRE COLOURS

- Active: Brown
- Neutral: Blue
- Earth: Green / Yellow
- Dimming Positive (+): As per wire label
- Dimming Negative (-): As per wire label
- Output (+): Red or as per wire label
- Output (-): Black or as per wire label

Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9




Wire Colors


- Active: Brown
- Neutral: Blue
- Earth: Green / Yellow
- Dimming Positive (+): As per wire label
- Dimming Negative (-): As per wire label
- Output (+): Red or as per wire label
- Output (-): Black or as per wire label

REMOTE DRIVER INSTALLATION (GLOBAL)


① (Full driver schematics on page 26)




② (Full instructions on page 16)




③




④



⑤




⑥




⚠ Before starting, determine which fasteners will be best suited to secure the fitting, based on the material of the ceiling substrate.

1. Licensed electrician to terminate Mains Power (A) / Dimming Control (C) to remotely mounted LED driver.
2. Hang shade from ceiling using mounting hardware provided. See page 14 for additional detail.
3. Mount canopy base to ceiling.
4. Insert DC output (A) from Driver into canopy base, then insert the DC input (B) from pendant or light source through canopy cover.
5. Licensed electrician to terminate DC input to DC output inside canopy.
6. Place canopy cover over canopy base (A), then fasten grub screws (B) and cable strain relief (C).



ON-BOARD DRIVER INSTALLATION (NORTH AMERICA)



⚠ This product is to be installed by a qualified electrician only

1. Hang shade from ceiling using mounting hardware provided. See page 16 for additional detail.
2. Mount canopy plate to junction box via screws
3. Licensed electrician to terminate Mains Power to Driver Input EldoLED Driver schematics on pg. 20, Meanwell Driver Schematics on page 21.
4. We recommend the use of twist-ons for these terminations.
5. Place canopy cover over canopy base (A), then fasten grub screws (B) and cable strain relief (C).

Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9




Caution, risk of electric shock

⚠ All electrical work, including the installation and wiring of drivers to be completed by a licensed electrician.

OTHER INFORMATION

- Indoor use only
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person




As its name indicates, the On-Board Driver option has the driver on board the pendant. Here's a quick overview of the wire colors for this option.

If you're looking for more information about the Canopy Concealed option, please refer to our index page.

Wire Colors

- (1) Hot/Live: Black
- (2) Neutral: White
- (3) Ground: Green
- (4) Dimming Positive (+): Purple or as per wire label
- (5) Dimming Negative (-): Grey or as per wire label



⚠ Before starting, determine which fasteners will be best suited to secure the fitting, based on the material of the ceiling substrate.

1. Hang shade from ceiling using mounting hardware provided. See page 14 for additional detail.
2. Mount canopy base to ceiling.
3. Insert DC output (A) from Driver into canopy base, then insert the DC input (B) from pendant or light source through canopy cover.
4. Licensed electrician to terminate DC input to DC output inside canopy.
5. Place canopy cover over canopy base (A), then fasten grub screws (B) and cable strain relief (C).

Luxxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9




Caution, risk of electric shock

⚠ All electrical work, including the installation and wiring of drivers to be completed by a licensed electrician.

OTHER INFORMATION

- Indoor use only
- The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person



As its name indicates, the On-Board Driver option has the driver on board the pendant. Here's a quick overview of the wire colors for this option.


If you're looking for more information about the Canopy Concealed option, where the driver is on board the canopy, please refer to our index page.

Wire Colors

- (1) AC Live: Brown
- (2) Neutral: Blue
- (3) Earth: Green-Yellow
- (4) Dimming Positive (+): Grey or as per wire label
- (5) Dimming Negative (-): Black or as per wire label

BRACE INSTALLATION INSTRUCTIONS (LARGE ONLY)

1. Place supplied braces over sheet metal tabs
2. Ensure braces overlap one another at frame arms
3. Use pliers to twist tabs 90° to secure braces.



Luxbox reserves the right to change the specification, material and colours at any time without notice. Standard warranty terms and conditions apply. All rights reserved. © May 2020 Ver 2.9